

3M COMPANY

3M PERFORMANCE LABEL MATERIALS, 1030 LAKE RD, MEDINA OH 44256

unprinted stock dsq: 7871(x), 7908(x)

Pressure-sensitive systems

Description: unprinted gloss white polyester facestock with adhesive which is protected by a release liner

Suitable for additional printing with one or more of the following inks (in the black color unless otherwise indicated);

Inkjet cartridge for use with CSAT iTS600 Printers

Agfa Agora G1, Agora G1 (All, Indoor use only), Agora G1 (Blue), Agora G1 (Red)

Inkjet cartridge for use with Durst Tau 150, Tau 150 8C and Tau 330 printers

Durst Tau (All)

Inkjet cartridge for use with Gamma printers

Atlantic Zeiser UV-A 20000 (All, Indoor use only)

Inkjet cartridge for use with Omega printers

Atlantic Zeiser UV-A 10000 (Indoor use only)

Inkjet cartridge with EFI Jetrion printers

EFI Jetrion Jetrion 4000 UV (All)

Thermal transfer ribbon

Armor AXR 600, AXR 7, AXR 7+, AXR 8, AXR 800

Astro-Nova R-5, RAF (Blue), RY

Autonics Co. Ltd. RP

Coding Products 5440 (Red), 5640 (Blue), 5940, 7996

Dainippon 4070, R300, R330, R510, R510 (Green), R510 (Red), R510 (White), R510 HF, R511, Signature Series (TM) Resin, Signature Series (TM) Wax, TR4070 (C), TR6070, TR6075 (C), TRX-55, V300

Dasco DR 74, DR 84

Dynic Corp. HL30 (C), HL32

Fujicopian FTX 308, TTM-245

Great Ribbon SDR

Honeywell Safety & Productivity Solutions TMX3702/HR04, TMX3710/HR03

ICS CC-4099.1

ITW B324

Iimak Primemark, SP330

Intermec Corp. 053258-2, 054048-4

Japan Pulp and Paper JP Resin 1, JP Resin 2 (Blue), JP Resin 2 (Green, Indoor use only), JP Resin 2 (Red, Indoor use only)

Kurz K500, K501

Markem 716 (Indoor use only)

Mid-City Columbia Inc. CGL 80, CGL 80HE, Matrix, MCC-14, MCC-23HE (G), NCR, PaceSetter, Promark II, Ultra V

NCR Matrix, PaceSetter, Promark II, Ultra V

Peak Ultra Extreme, Ultra Premium

Pelikan T016

Ricoh B100C (C), B110A, B110C, B110CX, B125CS

Sato Corp. Premier 1

Sony Chemicals 4075, 4085, 5070, TR5075

Toppan Printing Co. RP

Zebra Technologies Corp. 5095, 5100

Thermal transfer ribbon applied over Astro-Med "RY" black thermal transfe ribbon

Kurz K8151 (Clear)

Thermal transfer ribbon applied over Astro-Med "RY" black thermal transfer ink

Astro-Nova RRT (Clear)

Application Surface	Max Temp (°C)	Min Temp (°C)	Indoor Use	Outdoor Use	Additional Conditions
Acrylic paint	150	-40	Yes	Yes	-
Acrylic powder paint	150	-40	Yes	Yes	-
Alkyd paint	150	-40	Yes	Yes	-
Aluminum	150	-40	Yes	Yes	-
Epoxy paint	150	-40	Yes	Yes	G
Epoxy powder paint	150	-40	Yes	Yes	-
Epoxy powder paint (textured)	150	-40	Yes	Yes	-
Galvanized steel	150	-40	Yes	Yes	-
Polyester paint	150	-40	Yes	Yes	-
Polyester powder paint	150	-40	Yes	Yes	-
Polyester powder paint (textured)	150	-40	Yes	Yes	-
Polyethylene terephthalate	150	-40	Yes	Yes	-
Polyurethane powder paint	150	-40	Yes	Yes	-
Porcelain	150	-40	Yes	Yes	-
Stainless steel	150	-40	Yes	Yes	C

Nylon - Polyamide	100	-40	Yes	Yes	G
Phenolic - Phenol Formaldehyde	100	-40	Yes	Yes	-
Polybutylene terephthalate	100	-	Yes	No	-
Polycarbonate	100	-	Yes	No	-
PTFE coated metal	80	-	Yes	No	-
Polyphenylene oxide/ether	80	-40	Yes	Yes	-
Polypropylene	80	-	Yes	No	-
Polystyrene	80	-40	Yes	Yes	-
Zinc plated metal with chromate	80	-40	Yes	Yes	-
Acrylonitrile butadiene styrene	60	-40	Yes	Yes	-
Polyvinyl chloride	60	-40	Yes	No	-
Sabic "Valox 553"	150	-40	Yes	Yes	-

(x) - Optional code that is replaced by F, FL, HL, NF, or TL representing a flat (non-embossed) release liner
C - Occasional exposure to Cooking Oil (room temp).
G - Occasional exposure to Gasoline splashing.

Report Date: 1995-02-09
Last Revised: 2024-03-27

© 2024 UL Solutions

