



PRODUCT PAGE



Material: **ScotchCal™ Graphic Film Material 3698ED**

Overview:

3M™ ScotchCal™ Graphic Film Materials 3690E and 3698E are flexible cast vinyl films suitable for conforming to curved and textured surfaces, including most low surface energy plastics and small diameter applications. These film materials utilize 3M™ Adhesive 320 which offers high initial tack and excellent adhesion to a variety of surfaces including high surface energy (HSE) and low surface energy (LSE) plastics such as polyethylene.

Description:

3M™ ScotchCal™ Graphic Film Materials 3690E and 3698E are flexible cast vinyl films suitable for conforming to curved and textured surfaces, including most low surface energy plastics and small diameter applications. These film materials utilize 3M™ Adhesive 320 which offers high initial tack and excellent adhesion to a variety of surfaces including high surface energy (HSE) and low surface energy (LSE) plastics such as polyethylene.

Parameters:

Characteristics	Units	Value	Test Method
Series		320	
Application use		Labeling	
Type		Single sided tapes - Label	
Shape		Roll	
Application surfaces		HSE plastic, LSE plastic	
Adhesive type		Acrylic	
Backing liner		90gsm C2S Yellow Glassine Liner	
Operation temperatures	°C	-60 - 95	Thermometer

Warranty:**Technical data**

All information and statements contained in this document are based on the manufacturer's or material supplier's sources known to us at the time of filing. PERLON, spol. s r.o. believes them to be reliable in good faith, but the accuracy and/or completeness of such information is not guaranteed. The data should be considered representative or typical only and should not be used for specification purposes. Manufacturers reserve the right to make changes to the design, construction and technical data of products without prior notice.

Use of the product

Many factors beyond the control of PERLON, spol. s r.o. and known only to the user may affect the use and performance of materials in a particular application. Therefore, we recommend that the customer perform their own tests of the suitability and performance of the material for their application and to a responsible extent for reliable results. As a result, the customer is solely responsible for evaluating the product and determining if it is suitable for the customer's application, including evaluating workplace hazards and reviewing all applicable regulations and standards. Failure to properly evaluate, use, or comply with all applicable safety regulations may result in injury, illness, death, and/or property damage if the material and associated safety is not properly evaluated. PERLON, spol. s r.o. makes no warranties of fitness for a particular purpose.

Limitation of liability

PERLON, spol. s r.o. shall not be liable for any loss or damage arising out of or relating to the product material, whether direct, indirect, special, incidental or consequential (including, but not limited to, loss of products or business), regardless of the applicable legal practice, including but not limited to warranty, contract, negligence or strict liability.

www.convertimg.sk