



## PRODUCT PAGE



### Material: 3M™ Double Coated Tape 9495B

#### Overview:

3M™ Double Coated Tape 9495 stands up under tough conditions, yet provides stability and handles easily during processing. This double coated tape features a thin .5 mil black polyester film carrier coated on both sides with 3M™ Adhesive 200MP, excellent for graphics, nameplates and LED lens attachment. A 58-lb. PCK liner adds stability for efficient processing.

#### Description:

3M™ Double Coated Tape 9495 stands up under tough conditions, yet provides stability and handles easily during processing. This double coated tape features a thin .5 mil black polyester film carrier coated on both sides with 3M™ Adhesive 200MP, excellent for graphics, nameplates and LED lens attachment. A 58-lb. PCK liner adds stability for efficient processing.

#### Parameters:

Characteristics	Units	Value	Test Method
Series		200MP	
Application use		Labeling, Gaskets, Damping	
Type		Double sided tapes	
Shape		Roll	
Thickness	mm	0.14	Caliper
Application surfaces		HSE plastic, metal	
Carrier material		Black PET	
Adhesive type		Acrylic	
Color		Black	
Backing liner		58# Polycoated Kraft Paper (PCK)	
Operation temperatures	°C	-40 - 121	Thermometer
90° Peel Adhesion (on S. Steel at 22°C)	N/cm		ASTM D3330
90° Peel Adhesion (on ABS at 22°C)	N/cm	6.6	ASTM D3330

**Warranty:****Technical data**

All information and statements contained in this document are based on the manufacturer's or material supplier's sources known to us at the time of filing. PERLON, spol. s r.o. believes them to be reliable in good faith, but the accuracy and/or completeness of such information is not guaranteed. The data should be considered representative or typical only and should not be used for specification purposes. Manufacturers reserve the right to make changes to the design, construction and technical data of products without prior notice.

**Use of the product**

Many factors beyond the control of PERLON, spol. s r.o. and known only to the user may affect the use and performance of materials in a particular application. Therefore, we recommend that the customer perform their own tests of the suitability and performance of the material for their application and to a responsible extent for reliable results. As a result, the customer is solely responsible for evaluating the product and determining if it is suitable for the customer's application, including evaluating workplace hazards and reviewing all applicable regulations and standards. Failure to properly evaluate, use, or comply with all applicable safety regulations may result in injury, illness, death, and/or property damage if the material and associated safety is not properly evaluated. PERLON, spol. s r.o. makes no warranties of fitness for a particular purpose.

**Limitation of liability**

PERLON, spol. s r.o. shall not be liable for any loss or damage arising out of or relating to the product material, whether direct, indirect, special, incidental or consequential (including, but not limited to, loss of products or business), regardless of the applicable legal practice, including but not limited to warranty, contract, negligence or strict liability.

[www.convertimg.sk](http://www.convertimg.sk)