



## PRODUCT PAGE



### Material:

# EPDM T130 EP

### Overview:

MPG - EPDM T130 EP is a versatile synthetic rubber material, primarily composed of ethylene propylene diene monomer (EPDM). Known for its excellent resistance to weathering, ozone, UV rays, and extreme temperatures, it performs well in both outdoor and indoor environments. This material is also resistant to water, steam, and many chemicals, making it ideal for a variety of demanding applications.

### Description:

It is commonly used in industries such as construction, automotive, and engineering for sealing, insulation, and vibration damping purposes. MPG - EPDM T130 EP is particularly suitable for manufacturing gaskets, seals, and rubber profiles, providing reliable performance in harsh conditions while maintaining flexibility and durability over time.

### Parameters:

Characteristics	Units	Value	Test Method
Adhesive		Polyacrylic	
Carrier material		EPDM foam	
Color		Black	
Thickness	mm	2	
Operation temperature		-40 - 70	SAE J-2236 (max); ASTM D 746-98 (min)
Density		120	ASTM D 3574-95, Test A
Shore Hardness		55	ASTM D 2240-97
Compression set	%	< 20	ASTM D 3574-95
Compression Deflection	kPa	110	@ 25% Deflection
Tensile Strength	kPa	? 500	

**Warranty:****Technical data**

All information and statements contained in this document are based on the manufacturer's or material supplier's sources known to us at the time of filing. PERLON, spol. s r.o. believes them to be reliable in good faith, but the accuracy and/or completeness of such information is not guaranteed. The data should be considered representative or typical only and should not be used for specification purposes. Manufacturers reserve the right to make changes to the design, construction and technical data of products without prior notice.

**Use of the product**

Many factors beyond the control of PERLON, spol. s r.o. and known only to the user may affect the use and performance of materials in a particular application. Therefore, we recommend that the customer perform their own tests of the suitability and performance of the material for their application and to a responsible extent for reliable results. As a result, the customer is solely responsible for evaluating the product and determining if it is suitable for the customer's application, including evaluating workplace hazards and reviewing all applicable regulations and standards. Failure to properly evaluate, use, or comply with all applicable safety regulations may result in injury, illness, death, and/or property damage if the material and associated safety is not properly evaluated. PERLON, spol. s r.o. makes no warranties of fitness for a particular purpose.

**Limitation of liability**

PERLON, spol. s r.o. shall not be liable for any loss or damage arising out of or relating to the product material, whether direct, indirect, special, incidental or consequential (including, but not limited to, loss of products or business), regardless of the applicable legal practice, including but not limited to warranty, contract, negligence or strict liability.

[www.convertimg.sk](http://www.convertimg.sk)