



PRODUCT PAGE



Material:

T140 CR

Overview:

The T140 CR is a high-performance flame-retardant rubber material made from CR (neoprene), featuring a microporous structure with closed cells. It offers excellent durability, making it ideal for demanding applications that require resistance to external elements. This material is known for its superior ability to withstand aging, as well as exposure to harsh weather conditions and UV radiation. Additionally, it is designed to maintain flexibility and structural integrity in a wide range of temperatures.

Description:

In addition to its flame-retardant properties, the T140 CR provides robust resistance to ozone and oil, while offering moderate protection against acids. Thanks to its closed-cell structure, the material has low water absorption, making it suitable for environments where moisture resistance is essential. It meets the UL 94 HF1 flame-retardancy standard, making it a reliable choice for applications requiring both safety and durability, such as sealing, insulation, and vibration damping in harsh conditions.

Parameters:

Characteristics	Units	Value	Test Method
Adhesive		None	
Color		Black	
Thickness	mm	1.5	
Operation temperature		-30 - 100	SAE J-2236 (max); ASTM D 746-98 (min)
Density		140	ASTM D 3574-95, Test A
Shore Hardness		50	ASTM D 2240-97
Compression set	%	25	ASTM D 3574-95
Compression Deflection	kPa	110	@ 25% Deflection
Tensile Strength	kPa	? 250	

Warranty:**Technical data**

All information and statements contained in this document are based on the manufacturer's or material supplier's sources known to us at the time of filing. PERLON, spol. s r.o. believes them to be reliable in good faith, but the accuracy and/or completeness of such information is not guaranteed. The data should be considered representative or typical only and should not be used for specification purposes. Manufacturers reserve the right to make changes to the design, construction and technical data of products without prior notice.

Use of the product

Many factors beyond the control of PERLON, spol. s r.o. and known only to the user may affect the use and performance of materials in a particular application. Therefore, we recommend that the customer perform their own tests of the suitability and performance of the material for their application and to a responsible extent for reliable results. As a result, the customer is solely responsible for evaluating the product and determining if it is suitable for the customer's application, including evaluating workplace hazards and reviewing all applicable regulations and standards. Failure to properly evaluate, use, or comply with all applicable safety regulations may result in injury, illness, death, and/or property damage if the material and associated safety is not properly evaluated. PERLON, spol. s r.o. makes no warranties of fitness for a particular purpose.

Limitation of liability

PERLON, spol. s r.o. shall not be liable for any loss or damage arising out of or relating to the product material, whether direct, indirect, special, incidental or consequential (including, but not limited to, loss of products or business), regardless of the applicable legal practice, including but not limited to warranty, contract, negligence or strict liability.

www.converting.sk