

<b>Material:</b>	<b>PLEXIGLAS® XT White WN071 GT</b>
------------------	-------------------------------------

**Overview:**

PLEXIGLAS® XT White WN071 GT is an extruded acrylic sheet designed for versatility and high performance. With its elegant white finish, it provides a perfect solution for a variety of applications requiring translucence and durability

**Description:**

**Key Features:**

- **Light Transmission:** This material has a light transmission of approximately 30%, offering a soft, diffused light effect that is ideal for decorative and functional applications?
- **High Durability:** PLEXIGLAS® XT is known for its break resistance and surface hardness, making it suitable for environments where durability is essential?
- **Temperature Resistance:** It can withstand temperatures up to 70°C (158°F), ensuring performance in various conditions
- **UV Protection:** This acrylic sheet is UV absorbent, which helps prevent degradation and yellowing over time?
- **Easy to Process:** The material can be easily cut, drilled, and thermoformed, allowing for customized applications?.

**Applications:** Common uses include glazing in industrial settings, furniture design, shopfitting, exhibition booths, illuminated advertising, and displays. Its aesthetic appeal and practical properties make it a preferred choice for both commercial and residential projects

**Parameters:**

Characteristics	Units	Value	Test Method
Series		Plexiglass	
Thickness	mm	3	
Color		White	
Operation temperature	°C	-40 - 70	
Density	g/cm <sup>3</sup>	1.19 g/cm <sup>3</sup>	ISO 1183
Light Transmission	%	30	ISO 13468-2
Reflexive index	-	1.491	ISO 489
Tensile strength	MPa	72	ISO 527
Flexual strength	MPa	105	ISO 178
Impact strength	kJ/m <sup>2</sup>	15	
UV protection	-	1	
Type		Extruded	

**Warranty:****Technical data**

All information and statements contained in this document are based on the manufacturer's or material supplier's sources known to us at the time of filing. PERLON, spol. s r.o. believes them to be reliable in good faith, but the accuracy and/or completeness of such information is not guaranteed. The data should be considered representative or typical only and should not be used for specification purposes. Manufacturers reserve the right to make changes to the design, construction and technical data of products without prior notice.

**Use of the product**

Many factors beyond the control of PERLON, spol. s r.o. and known only to the user may affect the use and performance of materials in a particular application. Therefore, we recommend that the customer perform their own tests of the suitability and performance of the material for their application and to a responsible extent for reliable results. As a result, the customer is solely responsible for evaluating the product and determining if it is suitable for the customer's application, including evaluating workplace hazards and reviewing all applicable regulations and standards. Failure to properly evaluate, use, or comply with all applicable safety regulations may result in injury, illness, death, and/or property damage if the material and associated safety is not properly evaluated. PERLON, spol. s r.o. makes no warranties of fitness for a particular purpose.

**Limitation of liability**

PERLON, spol. s r.o. shall not be liable for any loss or damage arising out of or relating to the product material, whether direct, indirect, special, incidental or consequential (including, but not limited to, loss of products or business), regardless of the applicable legal practice, including but not limited to warranty, contract, negligence or strict liability.

[www.convertimg.sk](http://www.convertimg.sk)