

Material: PLEXIGLAS® GS Grey 7C83 GT

Overview:

PLEXIGLAS® GS Grey 7C83 GT is a high-quality cast acrylic sheet known for its striking grey color and excellent performance characteristics. This material combines aesthetic appeal with practical applications, making it suitable for various industrial and decorative uses.

Description:

Key Features:

- **Translucent Appearance:** With a light transmission of approximately 21%, this acrylic sheet offers a stylish translucent finish, allowing some light to filter through while providing privacy?
- **Durability:** PLEXIGLAS® GS Grey exhibits high break resistance and surface hardness, ensuring it can withstand impacts and wear?
- **Temperature Resistance:** This material is resistant to temperatures up to 80°C (176°F), making it suitable for diverse environments, including indoor and outdoor applications?
- **UV Protection:** The sheet is UV absorbent, which helps prevent degradation and yellowing over time, ensuring long-lasting clarity and color stability?
- **Easy Processing:** PLEXIGLAS® GS can be easily cut, drilled, and fabricated, allowing for customization in various projects?

Applications: This versatile acrylic sheet is ideal for use in glazing, furniture design, shopfitting, exhibition booths, illuminated advertising, and displays. Its combination of aesthetic appeal and functional properties makes it an excellent choice for both commercial and residential applications?

Parameters:

Characteristics	Units	Value	Test Method
Series		Plexiglass	
Thickness	mm	1	
Color		Dark grey	
Operation temperature	°C	-40 - 80	
Density	g/cm ³	1.19 g/cm ³	ISO 1183
Light Transmission	%	21	ISO 13468-2
Reflexive index	-	1.491	ISO 489
Tensile strength	MPa	80	ISO 527
Flexual strength	MPa	115	ISO 178
Impact strength	kJ/m ²	15	

UV protection	-	1	
Type		Cast	

Warranty:**Technical data**

All information and statements contained in this document are based on the manufacturer's or material supplier's sources known to us at the time of filing. PERLON, spol. s r.o. believes them to be reliable in good faith, but the accuracy and/or completeness of such information is not guaranteed. The data should be considered representative or typical only and should not be used for specification purposes. Manufacturers reserve the right to make changes to the design, construction and technical data of products without prior notice.

Use of the product

Many factors beyond the control of PERLON, spol. s r.o. and known only to the user may affect the use and performance of materials in a particular application. Therefore, we recommend that the customer perform their own tests of the suitability and performance of the material for their application and to a responsible extent for reliable results. As a result, the customer is solely responsible for evaluating the product and determining if it is suitable for the customer's application, including evaluating workplace hazards and reviewing all applicable regulations and standards. Failure to properly evaluate, use, or comply with all applicable safety regulations may result in injury, illness, death, and/or property damage if the material and associated safety is not properly evaluated. PERLON, spol. s r.o. makes no warranties of fitness for a particular purpose.

Limitation of liability

PERLON, spol. s r.o. shall not be liable for any loss or damage arising out of or relating to the product material, whether direct, indirect, special, incidental or consequential (including, but not limited to, loss of products or business), regardless of the applicable legal practice, including but not limited to warranty, contract, negligence or strict liability.

www.convertimg.sk