

<b>Material:</b>	<b>Plexi CRYLON UVT</b>
------------------	-------------------------

**Overview:**

Plexi CRYLON UVT is a high-quality acrylic sheet designed specifically for applications requiring enhanced UV transmission. It is particularly suitable for solariums and sunbeds due to its ability to allow significant amounts of UV-A and UV-B light to pass through while providing excellent resistance to degradation from exposure to UV rays?

**Description:**

Crylon® UVT is made from acrylic sheets (PMMA) and is designed for various applications. It offers excellent optical clarity and high transparency, making it suitable for both long-term and short-term external uses. Additionally, it features good UV and weathering resistance. The material supports established recycling procedures and can be processed through various methods like digital printing, screen printing, laminating, painting, laser cutting, drilling, engraving, thermoforming, and polishing, among others.

**Key Features:**

- **High UV Transmittance:** CRYLON UVT sheets have a light transmission of approximately 92%, allowing effective use in environments where UV exposure is essential?
- **Durability:** The material is engineered to resist weathering and aging, ensuring that it maintains its optical clarity and mechanical properties over time?
- **Versatility:** It can be used in a variety of applications, including advertising signs, display cases, furniture glazing, and partition walls?
- **Processing Capabilities:** CRYLON UVT can be easily handled and fabricated, allowing for printing, laminating, sawing, and laser cutting?

**Applications:** This material is ideal for:

- Solariums and tanning beds
- Displays in environments requiring UV light
- Signage and advertising where clarity and UV protection are important

**Parameters:**

Characteristics	Units	Value	Test Method
Series		Plexiglass	
Thickness	mm	2	
Color		Clear	
Operation temperature	°C	-20 - 80	
Density	g/cm <sup>3</sup>	1.19	ISO 1183
Light Transmission	%	92	ISO 13468-2

Reflexive index	-	1.492	ISO 489
Tensile strength	MPa	70	ISO 527
Flexual strength	MPa	110	ISO 178
Impact strength	kJ/m <sup>2</sup>	15	
UV protection	-	1	
Type		Extruded	

**Warranty:****Technical data**

All information and statements contained in this document are based on the manufacturer's or material supplier's sources known to us at the time of filing. PERLON, spol. s r.o. believes them to be reliable in good faith, but the accuracy and/or completeness of such information is not guaranteed. The data should be considered representative or typical only and should not be used for specification purposes. Manufacturers reserve the right to make changes to the design, construction and technical data of products without prior notice.

**Use of the product**

Many factors beyond the control of PERLON, spol. s r.o. and known only to the user may affect the use and performance of materials in a particular application. Therefore, we recommend that the customer perform their own tests of the suitability and performance of the material for their application and to a responsible extent for reliable results. As a result, the customer is solely responsible for evaluating the product and determining if it is suitable for the customer's application, including evaluating workplace hazards and reviewing all applicable regulations and standards. Failure to properly evaluate, use, or comply with all applicable safety regulations may result in injury, illness, death, and/or property damage if the material and associated safety is not properly evaluated. PERLON, spol. s r.o. makes no warranties of fitness for a particular purpose.

**Limitation of liability**

PERLON, spol. s r.o. shall not be liable for any loss or damage arising out of or relating to the product material, whether direct, indirect, special, incidental or consequential (including, but not limited to, loss of products or business), regardless of the applicable legal practice, including but not limited to warranty, contract, negligence or strict liability.

[www.convertimg.sk](http://www.convertimg.sk)