

Material:	AK521 LINER P 160 WH MR 1S
------------------	-----------------------------------

Overview:

A both sides PE-coated, white kraft liner with silicone on one side and medium release. This material is moisture stabilized and thus has got a excellent dimensional stability and lay-flatness. The PE-layer is protecting the paper against moisture. Self-adhesive products in large size sheets primarily used in the graphic industry. Excellent surface quality providing excellent adhesive clarity.

Description:

A both sides PE-coated, white kraft liner with silicone on one side and medium release

- **Applications and Use:** Suitable as a liner for adhesive coated facestocks when high dimensional stability is required.
- **Conversion and Printing:** Specially designed for high speed conversion, punching and perforation. Can be converted to reels or sheets.
- **Shelf Life:** To obtain optimal performance, use this product within two years of the date of manufacture, under storage conditions as defined by FINAT (20-25°C; 40-50%RH). Prolonged storage outside these conditions might reduce the shelf life

Parameters:

Characteristics	Units	Value	Test Method
Type		PET liner	
Color		White	
Thickness	mm	1.75	ISO 534
Basis Weigh	g/m ²	160	ISO 536
Shape		Sheet	
Coating		PE	

Warranty:**Technical data**

All information and statements contained in this document are based on the manufacturer's or material supplier's sources known to us at the time of filing. PERLON, spol. s r.o. believes them to be reliable in good faith, but the accuracy and/or completeness of such information is not guaranteed. The data should be considered representative or typical only and should not be used for specification purposes. Manufacturers reserve the right to make changes to the design, construction and technical data of products without prior notice.

Use of the product

Many factors beyond the control of PERLON, spol. s r.o. and known only to the user may affect the use and performance of materials in a particular application. Therefore, we recommend that the customer perform their own tests of the suitability and performance of the material for their application and to a responsible extent for reliable results. As a result, the customer is solely responsible for evaluating the product and determining if it is suitable for the customer's application, including evaluating workplace hazards and reviewing all applicable regulations and standards. Failure to properly evaluate, use, or comply with all applicable safety regulations may result in injury, illness, death, and/or property damage if the material and associated safety is not properly evaluated. PERLON, spol. s r.o. makes no warranties of fitness for a particular purpose.

Limitation of liability

PERLON, spol. s r.o. shall not be liable for any loss or damage arising out of or relating to the product material, whether direct, indirect, special, incidental or consequential (including, but not limited to, loss of products or business), regardless of the applicable legal practice, including but not limited to warranty, contract, negligence or strict liability.

www.converting.sk