



## PRODUCT PAGE



### Material:

### Autotex Fine F200

### Overview:

Autotex is a high quality textured polyester film, consisting of a base polyester and a flexible chemically bonded, UV-cured textured coating.

### Description:

Autotex is a high quality textured polyester film, developed for applications requiring a combination of flexibility with high abrasion and solvent resistance such as embossed membrane switches.

Autotex has an ink adhesion primer on the second surface. The standard 0-series ink-receptive coating is suitable for solvent based screen printing inks.

Autotex can be screen printed with Windotex windowing lacquers to obtain a clear window. Printing guidelines are available in the Windotex Processing and Safety Recommendations. Due to its lighter texture, Autotex Fine will produce clearer windows than Autotex Velvet.

### Parameters:

Characteristics	Units	Value	Test Method
Type		PET	
Shape		Roll	
Thickness	mm	0.2	
Tensile Strength	Mpa	160-250	ASTM D-882-91
Dielectric Strength	kV/mm	18.4	ASTM D-149-91
Elongation at break	%	125	ASTM D-882-91
Haze	%	60	ASTM D-1746
Volume resistance	? .CM	1.0*10 <sup>15</sup>	ASTM D257-83
Surface resistance	?	10*10 <sup>13</sup>	ASTM D257-83

**Warranty:****Technical data**

All information and statements contained in this document are based on the manufacturer's or material supplier's sources known to us at the time of filing. PERLON, spol. s r.o. believes them to be reliable in good faith, but the accuracy and/or completeness of such information is not guaranteed. The data should be considered representative or typical only and should not be used for specification purposes. Manufacturers reserve the right to make changes to the design, construction and technical data of products without prior notice.

**Use of the product**

Many factors beyond the control of PERLON, spol. s r.o. and known only to the user may affect the use and performance of materials in a particular application. Therefore, we recommend that the customer perform their own tests of the suitability and performance of the material for their application and to a responsible extent for reliable results. As a result, the customer is solely responsible for evaluating the product and determining if it is suitable for the customer's application, including evaluating workplace hazards and reviewing all applicable regulations and standards. Failure to properly evaluate, use, or comply with all applicable safety regulations may result in injury, illness, death, and/or property damage if the material and associated safety is not properly evaluated. PERLON, spol. s r.o. makes no warranties of fitness for a particular purpose.

**Limitation of liability**

PERLON, spol. s r.o. shall not be liable for any loss or damage arising out of or relating to the product material, whether direct, indirect, special, incidental or consequential (including, but not limited to, loss of products or business), regardless of the applicable legal practice, including but not limited to warranty, contract, negligence or strict liability.

[www.convertng.sk](http://www.convertng.sk)